

| | |
|--|---|
| <p>滤料: 诺美克斯/芳纶 (国产)</p> <p>Media: Nomex</p> <p>型号: BY-NX-613</p> <p>Item: BY-NX-613</p> <p>克重: 500 G</p> <p>Basis Weight: 500G</p> <p>拉力强度: 800/1000 N/5CM</p> <p>Breaking Strength: 800/1000 N/5CM</p> <p>透气量: 14.7 m³/m²/min</p> <p>Air Permeability: 14.7 m³/m²/min 持续运行温度: 204°C</p> <p>Continuous Operating Temperature: 204°C</p> <p>瞬间运行温度: 210°C</p> <p>Maximum Surge Temperature: 210°C</p> | <p>滤料: 诺美克斯/芳纶 (进口)</p> <p>Media: Nomex</p> <p>型号: BY-NX-614</p> <p>Item: BY-NX-614</p> <p>克重: 500 G</p> <p>Basis Weight: 500G</p> <p>拉力强度: 800/1000 N/5CM</p> <p>Breaking Strength: 800/1000 N/5CM</p> <p>透气量: 14.7 m³/m²/min</p> <p>Air Permeability: 14.7 m³/m²/min</p> <p>温度: 204°C</p> <p>Continuous Operating Temperature: 204°C</p> <p>瞬间运行温度: 210°C</p> <p>Maximum Surge Temperature: 210°C</p> |
| <p>滤料: Nomex mix 6</p> <p>型号: BY-NX-615</p> <p>Item: BY-NX-615</p> <p>克重: 550±15 G</p> <p>Basis Weight: 550±15G</p> <p>基布: 玻纤</p> <p>Scrim: fiberglass</p> <p>拉力强度: 1000/1100 N/5CM</p> <p>Breaking Strength: 1000/1100 N/5CM</p> <p>透气量: 14-17m³/m²/min</p> <p>Air Permeability: 14m³/m²/min</p> <p>温度: 160-170°C</p> <p>Continuous Operating Temperature: 160-170°C</p> <p>瞬间运行温度: 204°C</p> <p>Maximum Surge Temperature: 204°C</p> | <p>滤料: 诺美克斯 (芳纶) 混纺防静电</p> <p>Media: Anti-static Nomex blending</p> <p>型号: BY-NX-616</p> <p>Item: BY-NX-616</p> <p>克重: 500 G</p> <p>Basis Weight: 500G</p> <p>拉力强度: 800/1000 N/5CM</p> <p>Breaking Strength: 800/1000 N/5CM</p> <p>透气量: 14.7 m³/m²/min</p> <p>Air Permeability: 14.7 m³/m²/min</p> <p>温度: 160-170°C</p> <p>Continuous Operating Temperature: 160-170°C</p> <p>瞬间运行温度: 204°C</p> <p>Maximum Surge Temperature: 204°C</p> |