

<p>滤料:涤纶 Media:Polyester 型号: BY-PE-601 Item: BY-PE-601 克重:500 G Basis Weight:500 G 拉力强度:1000/1200 N/5CM Breaking Strength:1000/1200 N/5CM 透气量:15 m3/m2/min Air Permeability:15 m3/m2/min 持续运行温度: 130℃ Continuous Operating Temperature: 130℃ 瞬间运行温度: 150℃ Maximum Surge Temperature: 150℃</p>	<p>滤料:涤纶 防静电细条 二防 Media:Anti-static Polyester Slim Line water oil proof 型号: BY-PE-606 Item: BY-PE-606 克重:500 G Basis Weight:500 G 拉力强度:1000/1200N/5CM Breaking Strength:1000/1200 N/5CM 透气量:15 m3/m2/min Air Permeability:15 m3/m2/min 持续运行温度: 130℃ Continuous Operating Temperature: 130℃ 瞬间运行温度: 150℃ Maximum Surge Temperature: 150℃</p>
<p>滤料:涤纶 覆膜 Media:Polyester ePTFE 型号: BY-PE-602 Item: BY-PE-602 克重:500 G Basis Weight:500 G 拉力强度:1000/1200 N/5CM Breaking Strength:1000/1200 N/5CM 透气量:1.75m3/m2/min Air Permeability:1.7 5m3/m2/min 持续运行温度: 130℃ Continuous Operating Temperature: 130℃ 瞬间运行温度: 150℃ Maximum Surge Temperature: 150℃</p>	<p>滤料: 涤纶 防静电覆膜 Media:Anti-static Polyester ePTFE 型号: BY-PE-607 Item: BY-PE-607 克重:500G Basis Weight:500 G 拉力强度:1000/1200 N/5CM Breaking Strength:1000/1200 N/5CM 透气量:1.8 m3/m2/min Air Permeability: 1.8 m3/m2/min 持续运行温度: 130℃ Continuous Operating Temperature: 130℃ 瞬间运行温度: 150℃ Maximum Surge Temperature: 150℃</p>

滤料:涤纶 拒水防油

Media:Polyester water oil proof

型号: BY-PE-603

Item: BY-PE-603

克重:500 G

Basis Weight:500 G

拉力强度:1100/1300 N/5CM

Breaking Strength:1100/1300 N/5CM

透气量:15m³/m²/min

Air Permeability:15 m³/m²/min

持续运行温度: 130℃

Continuous Operating Temperature: 130℃

瞬间运行温度: 150℃

Maximum Surge Temperature: 150℃

滤料: 涤纶 混纺防静电

Media:Anti-static Polyester Blending

型号: BY-PE-608

Item: BY-PE-608

克重:500G

Basis Weight:500 G

拉力强度:1000/1200 N/5CM

Breaking Strength:1000/1200 N/5CM

透气量:14 m³/m²/min

Air Permeability: 14 m³/m²/min

持续运行温度: 130℃

Continuous Operating Temperature: 130℃

瞬间运行温度: 150℃

Maximum Surge Temperature: 150℃

滤料:涤纶 防静电宽条

Media: Anti-static Polyester Wide Line

型号: BY-PE-604

Item: BY-PE-604

克重:500 G

Basis Weight:500 G

拉力强度:1000/1200 N/5CM

Breaking Strength:1000/1200 N/5CM

透气量:15 m³/m²/min

Air Permeability:15 m³/m²/min

持续运行温度: 130℃

Continuous Operating Temperature: 130℃

瞬间运行温度: 150℃

Maximum Surge Temperature: 150℃